


Product Features

P1CA-29M29M-ST085-8 is an RF cable assembly that is part of P1dB's Tight-Flex™ cable assembly series. With a minimum bend radius of 0.2 inch, the cable allows bends at the connector end eliminating the need for a right angle connector. It is an 8 inch 2.92mm Male to 2.92mm Male cable assembly that utilizes ST085 Tight-Flex, triple shield coax, which is 0.104 inch (2.6 mm) diameter. The Tight-Flex™ cable assembly operates to 40 GHz with a max VSWR of 1.35:1. Max Insertion Loss at 40 GHz for this 8 inch assembly is 1.2 dB. RF shielding > 110 dB. Velocity of Propagation is 70 %.

Tight-Flex™ cable assemblies are a flexible version of RG405 semi-rigid and 085 conformable coax cables that meet RG405 dimensional and electrical specifications. Tight-Flex™ cable assemblies can operate up to 40 GHz, depending on the installed connectors. The advantage of Tight-Flex™ cables over other 085 flex cables is triple shield construction for great RF shielding and RF stability during tight bends.




Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		40.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	2.92mm Male	
Connector 2	2.92mm Male	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Coax Diameter	0.104	
Length	8.0	
RoHS Compliance	Yes	

Drawing



DIMENSIONS			
Center Conductor Diameter			
(inch)		0.0201	
(mm)		0.51	
Dielectric Diameter			
(inch)		0.0641	
(mm)		1.63	
Diameter Over Inner Foil			
(inch)		0.0708	
(mm)		1.80	
Diameter Over Outer Foil			
(inch)		0.0748	
(mm)		1.90	
Diameter over Braid			
(inch)		0.0885	
(mm)		2.25	
Jacket Diameter			
(inch)		0.104	
(mm)		2.64	
MATERIAL SPECIFICATIONS			
Jacket		FEP(BLUE)	
Braid		Round Silver Plated Copper	
Outer Foil		Aluminium Tape	
Inner Foil		Silver Plated Copper Tape	
Dielectric		Solid PTFE	
Center Conductor		Solid SPCW	
ELECTRICAL CHARACTERISTICS			
Impedance		50±2	
Capacitance (Nominal)			
(pF/ft)		29.4	
(pF/m)		96.4	
Velocity of Propagation (%)		70	
Cutt Off Frequency (GHz)		63	
Shielding Effectiveness		> -110dB	
Max. Attenuation	Attenuation		Power
Max Power (Watts)	dB/100Ft	dB/100M	
400MHz	14	45.9	240
1GHz	23	75.4	160
3GHz	39	128	80
5GHz	52	170.6	57
10GHz	80	262.4	44
18GHz	110	361	33
25GHz	131	430	29
30GHz	146	479	26
35GHz	160	525	23
40GHz	173	567	22
45GHz	183	600	20
50GHz	195	640	18

Product Notes

Temp range: -55 to +125 deg C

Minimum bend radius: 0.2 inch (5.1 mm)